

PROJECT NEWS

Kuala Lumpur Convention Centre

Kuala Lumpur, Malaysia

The Kuala Lumpur Convention Centre is located in the downtown area of Kuala Lumpur, as a leading international conference hall in Malaysia.

The five-story centre houses a large hall with a seating capacity of 3,000, an exhibition hall, a theatre and conference rooms. In this building, Fujitec installed 28 elevators including observation models featuring an innovative circular design, and 21 gracefully-designed escalators.

Fujitec products are widely used in the Centre where international conferences that are attended by many world's VIPs and exhibitions that attract people from around the world are held.

Owner:

Kuala Lumpur
Convention Centre Sdn. Bhd.

Architect:

Akitek Jururancang(M) Sdn. Bhd.

Contractor:

Sunway Construction Sdn. Bhd.



Kuala Lumpur Convention Centre

1. Site : Kuala Lumpur, Malaysia

2. Building : 7-Storey Convention Centre (5 above ground, 2 below ground)

3. Specifications

Elevators:

Use	Elevator Control	Capacity (kg)	Speed (mpm)	Stops/Floors	Units	Operation
P	AC-Geared (VVVF)	1,630	60	8/7	2	FLEX-N100 (2GSO)
P	AC-Geared (VVVF)	1,630	60	7/7	2	FLEX-N100 (2GSO)
P	AC-Geared (VVVF)	1,630	60	8/7	2	FLEX-N100 (2GSO)
P	AC-Geared (VVVF)	1,630	60	9/7	1	FLEX-N100 (2GSO)
P	AC-Geared (VVVF)	1,630	60	8/7	1	
P	AC-Geared (VVVF)	1,630	60	7/7	2	FLEX-N100 (2GSO)
P	AC-Geared (VVVF)	1,630	60	6/5	2	FLEX-N100 (2GSO)
P	AC-Geared (VVVF)	1,225	60	7/7	2	FLEX-N100 (2GSO)
P	AC-Geared (VVVF)	1,225	45	5/4	1	SC
P	AC-Geared (VVVF)	1,225	45	3/3	1	SC
P	AC-Gearless(VVVF)	1,020	60	2/2	1	SC
P	AC-Gearless (VVVF)	885	60	2/2	2	2SC
P	AC-Gearless (VVVF)	885	60	7/7	1	SC
P	AC-Gearless (VVVF)	885	60	5/5	1	SC
P	AC-Gearless (VVVF)	885	60	2/2	2	2SC
P	AC-Gearless (VVVF)	885	60	2/2	1	SC
P	AC-Gearless (VVVF)	1,020	60	2/2	1	SC
S	AC-Geared (VVVF)	7,000	30	11/8	1	SF
S	AC-Geared (VVVF)	7,000	30	7/7	1	SF
S	AC-Geared (VVVF)	7,000	30	9/7	1	SF

Total : 28 Units

(NOTES) P: Passenger
 S: Service
 VVVF: Variable Voltage Variable Frequency
 2GSO: 2-Car Group Supervisory Operation
 2SC: 2-Car Selective Collective Operation
 SC: 1-Car Selective Collective Operation
 SF: Single Automatic Operation

Escalators:

Type	Model	Speed (mpm)	Rize (mm)	Inclination	Units
GS8000-S	1200	30	9,880	30°	2
GS8000-S	1200	30	7,920	30°	2
GS8000-S	1200	30	6,950	30°	2
GS8000-S	1200	30	6,500	30°	2
GS8000-S	1200	30	6,000	30°	2
GS8000-S	1200	30	5,400	30°	2
GS8000-S	800	30	5,400	35°	2
GS8000-S	1200	30	5,150	35°	1
GS8000-S	1200	30	4,500	30°	2
GS8000-S	1200	30	4,000	30°	2
GS8000-S	1200	30	3,600	30°	2

Total : 21 Units

(NOTES) GS8000-S: Glass balustrade